



## Rope Access Pty Ltd T/AS Safety Roof Anchors

P: +61 2 9939 3523 F: +61 2 9939 7868  
PO Box 758, Freshwater NSW 2096

ABN: 67 147 756 670 ACN: 147 756 670

sales@safetyroofanchors.com.au  
www.safetyroofanchors.com.au

S.R.A. fully engineered product range

400 Series

Truss-T-Grip®

Profile Grips

Ladder Restraint Brackets

Fixings

### SPECIFICATION: SL01 STATIC LINE END ANCHOR POINT



#### **The System**

Anchorage is used as end anchor point for static lines in conjunction with SRA cone pedestal.

#### **Special Features:**

- Multipurpose anchor point
- Can be used for both Fall arrest/Rope access
- High breaking strain

#### **Uses:**

SL01 End anchor point can be used as end stanchion for static lines as well as individual anchorage point in accordance with AS/NZS 4488.2:2001 and 1891.4:2009

#### **Technical Data**

##### **Material Used:**

Investment Cast 316 Stainless Steel

##### **Finish:**

Bead Blast or E-Polished

##### **Ultimate Load:**

28 kN

##### **Dimensions:**

- Width – 38 mm
- Eye Diameter – 2 x 16 mm attachment hole

##### **Fixing Details:**

- 1 x Through bolt M12 (HOLE 14 DIA)
- 1 x Chemical HILTI HVU M12 (HOLE 14 DIA)

##### **Maintenance:**

Permanent installed anchorages inspection required by competent person at intervals not exceeding 12 months as specified in AS 1891.4:2009/AS/NZS 4488.2:1997

##### **Standards:**

Complies with - WHS Act 2011

Australian Standard – AS/NZS 1891.4:2009, AS/NZS 4488.2:2001