



**Rope Access Pty Ltd** T/AS **Safety Roof Anchors**

P: \*61 2 9939 3523 F: \*61 2 9939 7868  
PO Box 758, Freshwater NSW 2096

ABN: 67 147 756 670 ACN: 147 756 670

sales@safetyroofanchors.com.au  
www.safetyroofanchors.com.au

S.R.A. fully engineered product range

400 Series

Truss-T-Grip®

Profile Grips

Ladder Restraint Brackets

Fixings

## **SPECIFICATION: AA402HIS REMOVABLE EYE BOLT ANCHOR POINT**



### **The System**

Developed for applications in concrete AA402HIS eye bolt is rated at 15 kN. This internally threaded rod is suitable for applications that require removable eyebolt such as residential balconies or areas with increased trip hazard.

### **Special Features:**

- Unique robust design
- Complete traceability
- Hilti engineering

### **Uses:**

AA402HIS anchor is designed for industrial rope access (abseiling) and to support a fall arrest load of 15 kN provided a suitable personal shock absorber is used.

Installation by trained and certified personnel in accordance with AS/NZS 4488.2:1997 and AS/NZS 1891.4:2009 and manufacturer's instructions.

### **Technical Data**

#### **Material Used:**

Investment Cast 316 Stainless Steel (Eye)  
316 Stainless Steel (Hilti HIS internally threaded rod)

#### **Finish:**

Electro polished

#### **Abseil Capacity:**

12 kN

#### **Fall Arrest Capacity:**

15 kN

#### **Dimensions:**

- Overall length – 160mm
- Eye Diameter – 45 mm x 26 mm
- HIS anchor length – M12 x 110 mm
- Weight – 635 g

#### **Fixing Details:**

- Chemset 1 x HIS M12 (HOLE 22 DIA)

#### **Maintenance:**

Inspection and load testing required by competent person at intervals not exceeding 12 months as specified in AS 1891.4:2009 and AS/NZS 4488.2:1997

#### **Standards:**

Complies with WHS Act 2011 and relevant Codes of Practice.

Australian Standard – AS/NZS 1891.4:2009, AS/NZS 4488.2:1997, AS/NZS 5532:2013