



Rope Access Pty Ltd T/AS **Safety Roof Anchors**

P: *61 2 9939 3523 F: *61 2 9939 7868
PO Box 758, Freshwater NSW 2096

ABN: 67 147 756 670 ACN: 147 756 670

sales@safetyroofanchors.com.au
www.safetyroofanchors.com.au

S.R.A. fully engineered product range

400 Series

Truss-T-Grip®

Profile Grips

Ladder Restraint Brackets

Fixings

SPECIFICATION: SLTR static line traveller



The System

The SLTR static line traveller provides users with hands free, uninterrupted access along the whole length of static line system without the need to re-connect when passing intermediate brackets.

It features easy to operate, reliable locking gate mechanism and self locking karabiner.

Special Features:

- Easy operation and reliability
- Complete traceability
- Engineered and made in Australia

Uses:

The SLTR static line traveller is engineered for SRA static lines with 8mm (7x7 construction) 316 s/s cable.

Only the karabiner supplied with the unit must be used. The SLTR traveller is suitable for single person use only!

Operation by trained and certified personnel in accordance with AS/NZS 1891.4:2009, AS/NZS 1891.2:2001 and manufacturer's instructions.

Technical Data

Material Used:

Body: 316 Stainless Steel

Finish:

Electro polish

Dimensions:

- Overall length – 107mm
- Width – 55 mm
- Thickness: 28mm
- Eye Diameter – 15mm x 13 mm
- Weight – 590g

Maintenance:

Inspection required by competent person at intervals not exceeding 3 months.

Standards:

Complies with WHS Act 2011 and relevant Codes of Practice.

Australian Standard – AS/NZS 1891.2:2001