



Rope Access Pty Ltd T/AS Safety Roof Anchors

P: *61 2 9939 3523 F: *61 2 9939 7868
PO Box 758, Freshwater NSW 2096

ABN: 67 147 756 670 ACN: 147 756 670

sales@safetyroofanchors.com.au
www.safetyroofanchors.com.au

S.R.A. fully engineered product range

400 Series

Truss-T-Grip®

Profile Grips

Ladder Restraint Brackets

Fixings

SPECIFICATION: STP1 – Anchor Point Extension For Work At Height



The system

Stainless steel strop for use as a fall arrest anchor point extension for work at height.

Special Features:

- Rated 15 kN for fall arrest
- Swaged hard eyes at both ends
- Copper crimps covered with PVC
- Fall arrest rated Quicklink included

Uses:

STP is used as a fall arrest anchor point extension which can be supplied in multiple lengths typically:

- 1m (STP1)
- 2m (STP2)
- 3m (STP3)

STP can be customised to suit any required length.

Installation by trained and certified personnel in accordance with AS/NZS 1891.4:2009 and AS/NZS 5532:2013 and manufacturer's instructions.

Technical Data

Material Used:

- 316 Stainless Steel (wire rope, hard eyes and rated Quicklink)
- Copper crimps
- PVC polymer

Finish:

- Stainless steel with PVC coated swaged terminations

Dimensions:

- Steel rope – dia 6.4 mm
- Eyelet diameter – 22 mm
- Eye to eye length – 1000mm, 2000mm, 3000mm or custom
- Quicklink gate opening: 20mm