



## SPECIFICATION: AA400T EYE BOLT THROUGH BOLT ANCHOR POINT



### **The System**

Developed mainly for applications in concrete and steel AA400T eye bolt is designed to withstand a fall arrest load of 15 kN. It can be used for a wide range of applications and host structures.

### **Special Features:**

- Unique robust design
- Complete traceability
- Large 120mm dia plate to spread to load over larger surface area

### **Uses:**

AA400T anchor is designed for industrial rope access (abseiling) and to support a fall arrest load of 15 kN provided a suitable personal shock absorber is used.

Installation by trained and certified personnel in accordance with AS/NZS 4488.2:1997, AS/NZS 1891.4:2009, ISO 22846 (2003) and manufacturer's instructions.

### **Product Warranty:**

10 years from date of purchase subject to correct installation, use and maintenance in accordance with manufacturer's specifications and recommendations.

### **Important Note:**

Failure to supply and/or install proprietary product in accordance with above standards and codes, specifications and instructions voids complete system certification and/or warranty.

### **Technical Data**

#### **Material Used:**

Investment Cast 316 Stainless Steel (Eye)

316 Stainless Steel (Threaded Rod)

#### **Finish:**

Bead blast or electro polished

#### **Abseil Capacity:**

12 kN

#### **Fall Arrest Capacity:**

15 kN

#### **Dimensions:**

- Overall length – 300mm, 500mm or 1000mm
- Eye Diameter – 40 mm x 26 mm
- Rod length – M12 x 300 mm, 500mm or 1000mm
- Weight – 460 g

#### **Fixing Details:**

- 1 x Through bolt M12 (HOLE 14 DIA)

#### **Maintenance:**

Inspection and load testing required by competent person at intervals not exceeding 12 months as specified in AS 1891.4:2009, AS/NZS 4488.2:1997 and ISO 22846 (2003).

#### **Standards:**

Complies with WHS Act 2011 and relevant Codes of Practice.

Australian Standard – AS/NZS 1891.4:2009, AS/NZS 4488.2:1997, ISO 22846 (2003) and AS/NZS 5532:2013