



Rope Access Pty Ltd T/AS Safety Roof Anchors

P: *61 2 9939 3523 F: *61 2 9939 7868
PO Box 758, Freshwater NSW 2096

ABN: 67 147 756 670 ACN: 147 756 670

sales@safetyroofanchors.com.au
www.safetyroofanchors.com.au

S.R.A. fully engineered product range

400 Series

Truss-T-Grip®

Profile Grips

Ladder Restraint Brackets

Fixings

SPECIFICATION: AA404 Pedestal



The System

Developed for applications in concrete and steel AA404 Pedestal is used to support a swivel eye bolt or as a static line end anchor point carrier.

Special Features:

- Unique robust design
- Welded swivel eye bolt
- Complete traceability
- High profile design

Uses:

AA404 is useful in some applications where the extra height of the anchorage is important such as installations through topping.

Installation by trained and certified personnel in accordance with AS/NZS 4488.2:1997, AS/NZS 1891.4:2009, ISO 22846 (2003) and manufacturer's instructions.

Product Warranty:

10 years from date of purchase subject to correct installation, use and maintenance in accordance with manufacturer's specifications and recommendations.

Important Note:

Failure to supply and/or install proprietary product in accordance with above standards and codes, specifications and instructions voids complete system certification and/or warranty.

Technical Data

Material Used:

Investment Cast 316 Stainless Steel (Post and the Eye)
316 Stainless Steel (Bolt)

Finish:

Bead blast or electro polished

Abseil Capacity:

N/A

Fall Arrest Capacity:

N/A

Dimensions:

- Overall height – 100 mm
- Weight – 1,240 g

Fixing Details:

- 3 x Through bolt M12 (HOLE 14 DIA)
- 3 x Chemical HILTI HVU2 M12 (HOLE 14 DIA)

Maintenance:

Inspection and load testing required by competent person at intervals not exceeding 12 months as specified in AS 1891.4:2009, AS/NZS 4488.2:1997 and ISO 22846 (2003).

Standards:

Complies with WHS Act 2011 and relevant Codes of Practice.

Australian Standard – AS/NZS 1891.4:2009, AS/NZS 4488.2:1997, ISO 22846 (2003) and AS/NZS 5532:2013.