



## Rope Access Pty Ltd T/AS Safety Roof Anchors

P: \*61 2 9939 3523 F: \*61 2 9939 7868  
PO Box 758, Freshwater NSW 2096

ABN: 67 147 756 670 ACN: 147 756 670

sales@safetyroofanchors.com.au  
www.safetyroofanchors.com.au

S.R.A. fully engineered product range

400 Series

Truss-T-Grip®

Profile Grips

Ladder Restraint Brackets

Fixings

### SPECIFICATION: AA408 TENSILE ANCHOR POINT



#### **The System**

Developed especially for loading in tension AA408 features a double bolt design. This safety factor is important in all applications where the anchor is loaded under an angle exceeding 20° with the surface it is installed into (as per AS/NZS 4488.2:1997, section 5.3).

#### **Special Features:**

- Designed to be loaded in sheer and tension
- Large eye diameter
- Safety factor of 2 bolts

#### **Uses:**

AA408 anchor is designed for industrial rope access (abseiling) and to support a fall arrest load of 15 kN provided a suitable personal shock absorber is used.

It is essential in overhangs as a re-belay anchor or aid climbing anchor as well as a through bolt anchor with an added safety factor.

Installation by trained and certified personnel in accordance with AS/NZS 4488.2:1997, AS/NZS 1891.4:2009, ISO 22846 (2003) and manufacturer's instructions.

#### **Product Warranty:**

10 years from date of purchase subject to correct installation, use and maintenance in accordance with manufacturer's specifications and recommendations.

#### **Important Note:**

Failure to supply and/or install proprietary product in accordance with above standards and codes, specifications and instructions voids complete system certification and/or warranty.

#### **Technical Data**

##### **Material Used:**

Investment Cast 316 Stainless Steel

##### **Finish:**

Bead blast or Electro polish

##### **Abseil capacity:**

15 kN

##### **Fall arrest capacity:**

15 kN

##### **Dimensions:**

- Overall length - 240 mm
- Hole to hole centres - 200 mm
- Eye Diameter - 25 mm
- Weight - 710 g

##### **Fixing Details:**

- 2x Through bolt M12 (hole 14 DIA)
- 2x Chemical HILTI HVU2 M12 or equivalent (hole 14 DIA)
- 2x Chemical HILTI HVU2 M16 or equivalent (hole 18 DIA)
- 2x Hilti HSL-GR M10 (hole 15 DIA)
- 2x Hilti HST3-R M12 125mm (hole M12 DIA)
- 2x Friulsider FM-753 CRACK 120/20 M12 DIA

##### **Maintenance:**

Inspection and load testing required by competent person at intervals not exceeding 12 months as specified in AS 1891.4:2009, AS/NZS 4488.2:1997 and ISO 22846 (2003).

##### **Standards:**

Complies with WHS Act 2011 and relevant Codes of Practice.  
Australian Standard - AS/NZS 1891.4:2009, AS/NZS 4488.2:1997, ISO 22846 (2003) and AS/NZS 5532:2013.