



Rope Access Pty Ltd T/AS Safety Roof Anchors

P: +61 2 9939 3523 F: +61 2 9939 7868
PO Box 758, Freshwater NSW 2096

ABN: 67 147 756 670 ACN: 147 756 670

sales@safetyroofanchors.com.au
www.safetyroofanchors.com.au

S.R.A. fully engineered product range

400 Series


Truss-T-Grip®

Profile Grips

Ladder Restraint Brackets

Fixings

SPECIFICATION: BRC04 - WALLMOUNT LADDER RESTRAINT BRACKET



The System

Wallmount type ladder restraint bracket is designed to provide safe/secure attachment point to the extension ladders on roofs and structures where ladders would otherwise come in contact with the building's facade causing damage and unsafe access conditions.

Special Features:

- Unobtrusive
- Easy installation
- Extra deep design prevents ladder movement or slipping
- L – shape straps to enable installation on the wall

Uses:

Provides a secure point onto which a ladder can be attached to prevent movement or slipping.

Can be installed to concrete, masonry or metal vertical surfaces.

Technical Data

Material Used:

Body: 2mm 316 Stainless Steel

Straps: 3mm 316 Stainless Steel

Screws: 316 Stainless Steel

Finish:

Stainless Steel Polished smooth finish

Dimensions:

- Width 450mm

- Length 440mm

Weight:

2,510g

Fixing Details:

The ladder restraint bracket can be fixed/installed directly to the vertical masonry wall surface by using appropriate fixings.

Maintenance:

No scheduled maintenance required.

Standards:

Complies with current Codes of Practice.