

ROPE ACCESS PTY LTD T/AS SAFETY ROOF ANCHORS

www.safetyroofanchors.com.au

S.R.A. Fully Engineered Product Range | 400 Series | Allfits | Static Lines | Profile Grips | Ladder Restraint Brackets | Fixings



PGI PROFILE GRIP SURFACE MOUNT ANCHOR POINT AUSTRALIAN PATENT 2004218599

The System

Profile Grip PG1 is a top fixed anchor point designed for an exact fit specifically to Longline305 roof sheet profile. The tailored fit in conjunction with 360° swivel action dramatically improves the loading properties of this surface mount anchor.

Special Features:

- Swivelling anchor point
- Easy installation doesn't require access to the underside of roof
- Unique way of fixing works in unison with the host structure
- Suitable for abseiling and fall arrest
- Suitable for both steel and timber structures

Uses:

Designed for industrial rope access (abseiling) and to support a fall arrest load of 15 KN in any direction (always in sheer) provided a suitable personal shock absorber is used.

Installation by trained and certified personnel in accordance with AS/NZS 4488.2:1997 and AS/NZS 1891.4:2009 and manufacturer's instructions.

Technical Data

Material Used:

Profile Grip plate: 3mm grade 316 stainless steel Swivel anchor: Investment cast 316 Stainless Steel

Finish:

Profile Grip plate – 2B Stainless Swivel anchor- Electro polish Profile Grip plates can be supplied in any Colorbond colour

Ultimate Load:

15 kN

Dimensions:

- Length of plate 300 mm
- ✓ Eye Diameter 25 mm
- Weight 2,725 Kg

Fixing Details:

- Timber rafter/ batten min 70mm x 35mm
- ✓ Steel Purlin min gauge 150 x 1.2 mm
- Roof Sheet min gauge 0.42mm

Maintenance:

Inspection required by competent person at intervals not exceeding 12 months as specified in AS 1891.4:2009 and ISO 22846 (2003)

Standards:

Complies with WHS Act 2011 and relevant Codes of Practice. Australian Standard – AS/NZS 1891.4:2009, AS/NZS 4488.2:1997, ISO 22846 (2003) and AS/NZS 5532:2013