



Rope Access Pty Ltd T/AS Safety Roof Anchors

P: *61 2 9939 3523 F: *61 2 9939 7868
PO Box 758, Freshwater NSW 2096

ABN: 67 147 756 670 ACN: 147 756 670

sales@safetyroofanchors.com.au
www.safetyroofanchors.com.au

S.R.A. fully engineered product range

400 Series

Truss-T-Grip®

Profile Grips

Ladder Restraint Brackets

Fixings

SPECIFICATION: PSL01 STATIC LINE END ANCHOR POINT (CONCRETE MOUNT)



The System

Anchorage is used as an end anchor point for static line installations in concrete.

Special Features:

- Robust design
- Full traceability
- Fully engineered and independently tested

Uses:

PSL01 can be used as a static line end anchor point or as a bracing to add strength to existing static line end anchor point.

Technical Data

Material Used:

Investment Cast 316 Stainless Steel

Finish:

E-Polished

Ultimate Load:

28 kN

Dimensions:

- Height – 150 mm
- Eye Diameter – 2 x 16 mm attachment hole
- Weight – 1,565 g

Fixing Details:

- 1 x Through bolt M12 (hole 14 DIA)
- 1 x Chemical HILTI HVU M12 or equivalent (hole 14 DIA)

Maintenance:

Permanent installed anchorages inspection required by competent person at intervals not exceeding 12 months as specified in AS 1891.4:2009/AS/NZS 4488.2:1997

Standards:

Complies with - WHS Act 2011

Australian Standard – AS/NZS 1891.4:2009, AS/NZS 4488.2:2001