

TRUSS-T-GRIP® ANCHOR

INSTALLATION INSTRUCTIONS

Things To Know:

Truss-T-Grip® anchor points have been designed for applications in both rope access (abseiling) and fall arrest. They will withstand loads of 15 kN in all directions when installed according to our instructions. Keep in mind that common size trusses and rafters on their own are not strong enough to withstand the lateral force of 15 kN and that's why the structure must be reinforced as described below!

Truss-T-Grip anchor points are stocked in 3 most common rafter sizes but can be manufactured to accommodate any rafter size. They can be installed permanently or temporarily, depending on requirements. All types of Truss-T-Grip are supplied with Roof-tite flashing and Armour plates to provide for permanent installation.

- **Timber truss/rafter size:** 90mm x 35mm, 100mm x 50mm, 200mm x 50mm
- **Loading:** Truss-T-Grip anchor points can be loaded in all directions always in sheer with the roof.




Tools and Materials Needed:


Hammer, 2 ring spanners, hand saw, grinder with diamond wheel, caulking gun, Stanley knife, Wakaflex or similar flashing, framing pine to reinforce roof structure (point 6)

Installation Steps:


1. Remove tiles to expose the rafter.



2. Place Truss-T-Grip body on the rafter.



3. Install the U-straps with friction plates to the underside of the rafter ensuring the Armour plates are held firmly against the rafter. The anchor body shape provides for attachment of two sizes of friction plates at two different spots. Ensure the correct pair of holes on the anchor body is used for fixing. They are 35mm or 50mm wide (this depends on the rafter size) and attach with M8 bolts (provided). You can choose to work from the inside the roof cavity or from the roof top. A team of two is ideal with one person inside and one outside.



4. Use a hammer to knock the friction plates into compression and tighten the bolts.



5. Install 2 small nails (provided) next to the friction plates to keep them engaged at all times.



6. Extra nogging between the rafters cut to size must be used to strengthen the roof structure. A piece of pine the size of the rafter will do the job perfectly (shown in red).



7. Use angle grinder with a diamond wheel to make a small hole in the tile, positioned directly above the anchor eye. Ensure the hole will be in the correct position by partially replacing the tile and marking the position with a texter. Once the position has been determined cut the outline of a rectangular hole connecting the diagonally opposite corners of the hole with two cuts in the shape of letter X. Then tap the tile gently with a hammer creating a rectangular hole. Replace all tiles and close the hole in the roof.



8. Apply Wakaflex or similar flashing over the tile and cut to size with Stanley knife.



9. Apply polyurethane sealant under the Roof-tite flashing (provided) and shape the base of the flashing to adhere to the tile's shape perfectly.



10. The installation is now complete.



Annual Re-certification:

All anchor points must be inspected and certified before their initial use and subsequently on regular basis to satisfy the requirements set out in AS/NZS 1891.4:2009, AS/NZS 4488.2:1997 and ISO 22846 (2003).

Note:

The roof structure must be assessed by a structural engineer unless it is clear to a suitably qualified person that it is capable of withstanding the forces imposed on it during arresting of a fall and during work positioning.

Disclaimer:

All product specifications and technical descriptions, recommendations and other information provided in this document are given as general guidance and advice, and are to be considered in conjunction with Safety Roof Anchors installation instructions and any other data available and applicable to each particular standard product or system. Use of such data is however the user's sole responsibility taking into account the intended application and actual conditions existing on the specific worksite. Consequent selection of the right product for any particular use remains the user's ultimate responsibility.

Safety Roof Anchors is therefore not obligated or liable for any direct or indirect, incidental or consequential damages, losses or expenses in connection with, or by reason of the suitability and use of or otherwise, any product or system for any purpose. Implied warranties of merchantability or fitness for any particular purpose are specifically excluded. Safety Roof Anchors maintains a policy of continuous improvement and development, and therefore reserves the right to modify, amend or otherwise alter product and system designs and specification, models and part numbers, colours and pricing etc., without prior notice. Safety Roof Anchors accepts no liability whatsoever for incorrect information, errors or omissions.