

## **Rope Access Pty Ltd T/As Safety Roof Anchors**

P: **\*61 2 9939 3523** F: **\*61 2 9939 7868** PO Box 758, Freshwater NSW 2096 ABN: 67 147 756 670 ACN: 147 756 670 sales@safetyroofanchors.com.au www.safetyroofanchors.com.au

S.R.A. fully engineered product range

**400 Series** 

Truss-T-Grip®

**Profile Grips** 

**Ladder Restraint Brackets** 

**Fixings** 

# SPECIFICATION: PG2 PROFILE GRIP SURFACE MOUNT ANCHOR POINT AUSTRALIAN PATENT 2004218599



## **The System**

Profile Grips are top fixed anchor points designed for exact fit to all metal deck roofs commonly used in Australia. Profile Grip PG2 is tailored to fit specifically to Brownbilt (LongLine 305) roof sheet profile. The tailored fit in conjunction with 360° swivel action dramatically improves loading properties of this surface mount anchor.

#### **Special Features:**

- Swivelling anchor point
- Easy installation doesn't require access to the underside of roof
- Unique way of fixing works in unison with the host structure
- Suitable for abseiling and fall arrest
- Suitable for both steel and timber structures

## Uses:

Designed for industrial rope access (abseiling) and to support a fall arrest load of 15 KN in any direction (always in sheer) provided a suitable personal shock absorber is used.

Installation by trained and certified personnel in accordance with AS/NZS 4488.2:1997 and AS/NZS 1891.4:2009 and manufacturer's instructions.

### **Technical Data**

#### **Material Used:**

Profile Grip plate: 3mm grade 316 stainless steel

Swivel anchor: Investment cast 316 Stainless Steel

#### Finish:

Profile Grip plate - 2B Stainless Steel

Swivel anchor - Electro polish

Profile Grip plates can be supplied in any Colorbond colour

## **Ultimate load:**

15 kN

#### Dimensions:

- Length of plate 300 mm
- Eye Diameter 25 mm
- Weight 3,080 Kg

#### **Fixing Details:**

- Timber rafter/ batten min 70mm x 35mm
- Steel Purlin min gauge 150 x 1.2 mm
- Roof Sheet min gauge 0.42mm

## Maintenance:

Inspection required by competent person at intervals not exceeding 12 months as specified in AS 1891.4:2009 and AS/NZS 4488.2:1997

## Standards:

Complies with WHS Act 2011 and relevant Codes of Practice.

Australian Standard – AS/NZS 1891.4:2009, AS/NZS 4488.2:1997, AS/NZS 5532:2013